



0.1m 線出し量 : 0.19

| 1/3" F1.8/4.5mm | |
|---------------------------|----------------------------------|
| FOCAL LENGTH | f=4.5mm |
| MAX. DIAMETER (RATIO) | F=1:1.8~11 |
| PICTURE SIZE | 3.6x4.8mm |
| ANGLE | VER. ANGLE 45.0° |
| | HOR. ANGLE 59.2° |
| | DIA. ANGLE 72.5° |
| DISTORTION (TV) | -2.8% |
| SHOOTING RANGE AT | VER. 89mm |
| MINIMUM FOCUS | HOR. 122mm |
| DISTANCE | DIA. 158mm |
| MINIMUM FOCUS DISTANCE | 0.1m |
| FLANGE BACK | 12mm in air |
| BACK FOCUS | 8.11mm in air |
| FILTER SCREW SIZE | --- |
| FRONT/REAR EFFECTIVE DIA. | F. ϕ 12.4mm R. ϕ 6.4mm |
| MOUNT | NF-MOUNT (M17x0.75) |
| EXIT PUPIL | -44.3mm |
| TEMPERATURE RANGE | -10~+50°C |
| STORNG TEMPERATURE RANGE | -20~+60°C |
| WEIGHT | 35g |

| | | | | | | | |
|----------|-------|-----|-----------------|----|----|---|----|
| | | 尺度 | 1/1 | 承認 | 八木 | 製 | 富永 |
| | | 機種名 | S10-240 | | | | |
| | | 機種番 | 1/3" F1.8/4.5mm | | | | |
| 10.08.09 | 作成年月日 | | | | | | |