



| 1" 1.4/12.5mm | | 2/3" | 1/2" |
|---------------------------|------------------|---------|---------|
| FOCAL LENGTH | f=12.5mm | | |
| MAX. DIAMETER (RATIO) | F=1:1.4~16 | | |
| PICTURE SIZE | 12.8x9.6mm | 8.8x6.6 | 6.4x4.8 |
| ANGLE | VER. ANGLE | 42.5° | 29.5° |
| | HOR. ANGLE | 55.6° | 39.1° |
| | DIA. ANGLE | 67.7° | 48.3° |
| DISTORTION (TV) | -1.58% | -1% | -0.6% |
| MINIMUM FOCUS DISTANCE | 0.3m | | |
| FLANGE BACK | 17.526 mm in air | | |
| BACK FOCUS | 12.6mm in air | | |
| FILTER SCREW SIZE | M27x0.5 | | |
| FRONT/REAR EFFECTIVE DIA. | φ28.1mm | φ17.5mm | |
| MOUNT | C-MOUNT | | |
| EXIT PUPIL | -45.9mm | | |
| TEMPERATURE RANGE | -10~+45° C | | |
| STORNG TEMPERATURE RANGE | -40~+60° C | | |
| | | | |
| | | | |

| | | |
|--|--|------------------|
| | | LM12HC |
| | | |
| | | |
| | | 1" F1.4 f=12.5mm |