



2/3" 1.4/12mm C		1/2"	1/3"
Focal Length		f=12mm±5%	
Max. Diameter (Ratio)		F=1 : 1.4±5%	
Element		6 Group 6 Elements	
Picture Size		6.6x8.8mm	3.6x4.8
Angle	Ver.	31.7°	17.2°
	Hor.	42.5°	23.0°
	Dia.	53.7°	28.8°
Distortion (TV)		-2.5%	-0.6%
Shooting Range at M.O.D.	Ver.	173mm	92.2mm
	Hor.	237mm	123.8mm
	Dia.	307mm	156.2mm
Minimum Object Distance		0.3m +0.13	
Flange Back		17.526 -0 mm in air	
Back Focus		11.12mm in air	
Filter Screw Size		M30.5x0.5	
Front/Rear Effective Dia.		F: φ12.3mm	R: φ11.7mm
Mount		C-MOUNT	
Exit Pupil		-38.9mm	
Temperature Range		-10~+45° C	
Storage Temperature Range		-40~+60° C	
Resolution		Center: 100 LP/mm	Corner: 40LP/mm
Stopper Strength		10kgf · cm	
Endurance Tests		Iris: 5,000Times	Focus: 5,000Times
Operating Torque		Iris: 50~600gf · cm	Focus: 100~1000gf · cm
Weight		53g±5g	

LM12JCR